

CERTIFICATE

No. P15220435





Order No. 294025

Product Power Supply, Open frame Building-in Type Astec International Ltd. Applicant 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon Hong Kong Manufacturer Astec International Ltd. 16th Floor, Lu Plaza, 2 Wing Yip Street, Kwun Tong, Kowloon Hong Kong Factory ✓ See page 2 Ratings 1.6A 100-250V 50/60/440Hz or 1.0A 120V-300V DC Trade mark LPT46 Model / Type Ref. Principal characteristics Cl. I, DC-outputs: 5A +5V, 1.5A +24V, 0.7A +12V. Maximum Continuous Output Power 40W convection cooling. Maximum Continuous Output Power 55W with 30CFM forced air. See next page(s) A sample of the product was tested **OFF** EN 60950-1:2006;A11;A1;A12;A2 and found to be in conformity with This certificate documents conformity with the standards shown, and also applies as license for Validity use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary. Additional information See next page(s) The abovementioned certified equipment complies with current regulatory requirements regarding electrical safety in Norway and other EU/EEA member states, as far as this can be checked. Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system. See next page(s) Additional model(s)

Date of issue 04-11-2015

Nastavan Vendoodi

Nastaran Vadoodi Certification Department

Nemko AS



CERTIFICATE

No. P15220435





Order No. 294025 Page 2/2

Product Power Supply, Open frame Building-in Type

Pos. No 1

Model / Type Ref. LPT47

Trade mark (if different from page 1)

Rating 1.6A 100-250V 50/60/440Hz or 1.0A 120V-300V DC

Principal characteristics Cl. I, DC-outputs: 5A +5V, 1.5A +24V, 0.7A -12V. Maximum Continuous

Output Power 40W convection cooling. Maximum Continuous Output Power

55W with 30CFM forced air.

Product Power Supply, Open frame Building-in Type

Pos. No 2

Model / Type Ref. LPT48

Trade mark (if different from page 1)

Rating 1.6A 100-250V 50/60/440Hz or 1.0A 120V-300V DC

Principal characteristics Cl. I, DC-outputs: 5A +5V, 1.5A +24V, 0.7A -5V. Maximum Continuous

Output Power 40W convection cooling. Maximum Continuous Output Power

55W with 30CFM forced air.

Factories:

Astec Power Philippines Inc.

Astec Power Philippines Inc.

Main Avenue Corner Road "J" Cavite Export Processing 104 Laguna Blvd., Laguna Technopark, Sta. Rosa

Laguna, 4026 Philippines

Philippines

Zone Rosario, Cavite, 4106

Date of issue 04-11-2015

Nastaran Vadoodi

Certification Department

Nemko AS